

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : A61B 17/72	A1	(11) International Publication Number: WO 00/27298 (43) International Publication Date: 18 May 2000 (18.05.00)
(21) International Application Number: PCT/BG99/00025 (22) International Filing Date: 11 November 1999 (11.11.99) (30) Priority Data: 102912 11 November 1998 (11.11.98) BG (71)(72) Applicant and Inventor: IGNATOV, Nikola Gueorguiev [BG/BG]; Victor Grigorovich Street, 12, 1606 Sofia (BG).	(81) Designated States: JP, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.	

(54) Title: INTRAMEDULLARY DEVICE FOR FIXATION, COMPRESSION AND TRACTION

(57) Abstract

The device consists of two metal tubes (4) and (5) one inside the other. The inner tube or slider (5) has in its top end threads with a feed screw (1) situated therein. The screw (1) passes through a bearing (2) welded to the outer tube (4), and under and above the bearing there is a stopper (3). There are holes drilled in the opposite walls of the outer tube (4) immediately under the bottom end of the screw (1). Under the holes, bilaterally on the outer tube (4), there are longitudinal slots. On the slider (5) there are holes of the same size as those on the outer tube (4), and above them, longitudinal slots cut bilaterally and having a size corresponding to that of the slots on the outer tube (4). The holes on the outer tube are disposed opposite the slots on the slider, while the holes on the slider are disposed opposite the slots on the outer tube. The device can serve for fixation, compression and traction rather than only passive fixation.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

WO 00/27298

PCT/BG99/00025

INTRAMEDULLARY DEVICE FOR FIXATION, COMPRESSION AND TRACTION

Field of the Invention

The invention relates to an intramedullary device for fixation, compression and traction of the femur in the treatment of various kinds of fractures, and is used in the field of orthopaedics and traumatology.

Prior Art

It is known that for the treatment of various kinds of fractures of the femur, in addition to metal plates and screws for fixation of the bone fragments, there are used also different Kuntscher and other nails for intramedullary fixation.

One of the most frequent complications that occur when using plates and screws is the bending or breaking thereof, resulting in deformation or non-union of the bone. The fixation here is static. One of the weak points of the medullary nails is that they cannot always ensure stability of the fragments, and there is always a risk of their dislocation. For the purpose of increasing the stability of the fracture site, surgeons started to ream the medullary canal in order to insert tight fitting nails. However, later investigations showed that reaming of the medullary canal leads to severe damage of its blood supply.

In order to avoid this negative moment of the intramedullary osteosynthesis, the so-called interlocking nails have recently been invented and applied, said nails having holes in their top and bottom ends. Screws are inserted through the proximal and the distal fragments and respectively through the holes of the medullary nails. Thus the fragments get blocked and the above-mentioned dislocations are avoided. This is what the inventors call static fixation. If no transverse screw is inserted through one of the fragments, it gets free and axially pressed to the fixed fragment, this being

WO 00/27298

PCT/BG99/00025

called dynamic fixation. According to this method, the static fixation cannot ensure an adequately close and continuous contact between the fragments, and in the so-called dynamic fixation one of the fragments is unstable. The interlocking intramedullary nails are most suitable for comminuted fractures of the long bones needing static fixation.

Along with the above-mentioned osteosynthetic devices, the so-called external fixators are also used in practice. In this case, a great number of Kirschner wires or pins are inserted through the skin into the fragments, the outer ends of said pins being affixed to a system of metal planes, rods and screws placed outside the human body. This system moves the wires or pins, and the fragments together with them, to one or another direction. The external fixators are used for the treatment of some kinds of fresh fractures, delayed union and non-union of fractures, lengthening or shortening of limbs, and some other orthopaedic cases. They are useful also in the treatment of infected fractures.

The most essential disadvantages of the external fixators are:

- development of pin tract infections;
- it may be difficult for surgeons who are not well acquainted with the fixators to assemble them;
- the fixators often are coarse, cumbersome and uncomfortable for the usual clothes of the patients;
- there is a risk of refractures after removing the fixator, therefore there is a necessity of an additional external protection of the leg until the full consolidation of the bone, which may take a lot of time;
- imprudent and improvident patients may damage the apparatus;
- restraint of the muscles from their normal excursion, muscle fibrosis and a risk of tendon rupture.

In some types of fixators:

- it is inconvenient to perform additional open procedures in the region of the pathological site; besides there is an additional risk in case of infection along the pins tract;

WO 00/27298

PCT/BG99/00025

- impossibility, or limited possibility for correction of dislocations of the fragments. Besides, additional skills and efforts are required for that purpose.

Technical Substance

The device consists of two metal tubes with different diameters, situated coaxially one inside the other and having a profile similar to that of a Kuntscher nail. In the top inside end of the inner metal tube or slider there are threads with a screw situated therein, whose length may vary depending on the case. The top end of the screw passes through a bearing welded to the outer tube, a stopper being situated under and above the bearing. Immediately under the bottom end of the screw, on the two opposite walls of the outer tube, there are drilled transverse holes at an equal distance (1-2 cm) from each other. Under the distal hole there is a longitudinal slot on each of the two sides of the outer tube, the length of which can vary. The slider also has holes of the same size as those on the outer tube, but in its distal part. Above the holes, there are longitudinal slots cut bilaterally on the slider and having a size corresponding to the slots on the outer tube. Thus the holes on the outer tube are disposed exactly opposite the slots on the slider, and the holes on the slider are disposed the same way opposite the slots on the outer tube. The top end of the outer tube is cylindrical and has outside threads at a length of approximately 1 cm.

Description of the Figures Enclosed

Fig. 1. represents a scheme of the principles of operation of an intramedullary device for fixation, compression and traction of the femur.

WO 00/27298

PCT/BG99/00025

Embodiments

According to an embodiment of the invention, an intramedullary device for fixation, compression and traction of the femur consists of two metal tubes (4, 5) with different diameters, coaxially disposed one inside the other. Both tubes have a profile similar to that of a Kuntscher nail. The inner tube or slider (5) has in its top end threads with a feeding screw (1) disposed therein. The top end of the screw (1) passes through a bearing (2) welded to the outer tube, and under and above the bearing there is disposed a stopper (3). Immediately under the bottom end of the screw (1) there are transverse holes drilled on the opposite sides of the outer tube (4) at an equal distance (1-2 cm) from each other. Under the distal hole there is a longitudinal bilateral slot cut on the outer tube (4), whose length may vary. The slider (5) also has holes of the same size as those on the outer tube, but in its distal part. Above them, there are bilateral longitudinal slots on the slider having a size corresponding to the slots on the outer tube. Thus the holes on the outer tube are disposed exactly opposite the slots on the slider, while the holes on the slider are disposed the same way opposite the slots on the outer tube. The top end of the outer tube is cylindrical and has outside threads at a length of 1 cm.

Application of the Invention

The construction of the present device allows a telescoping movement of the inner tube towards the outer one. When the device is applied in the region of the femur, the system comprising the two tubes and the feeding screw is introduced into the medullar canal of the two fragments by means of a tubular driver, which is screwed on the top end of the outer tube. After that, by means of a target device, through the proximal and the distal fragments there are inserted one or two (depending on the case) transverse screws having a diameter of 5 mm (6) and passing through the two opposite walls of the bone (7) and through the respective holes and slots on the metal

WO 00/27298

PCT/BG99/00025

tubes as well. So installed, the system can serve as a static fixator like the interlocking nails. When it is necessary to create forces of compression or traction of the fragments, the surgeon turns the longitudinal screw to one or another direction by means of a screw driver placed through the tubular driver. Due to the constantly acting forces of compression or traction in the system, the latter is rather stable, so that the surgeon does not have to try to insert it tightly into the femur canal in every case. The proper length of the device applied is to be complied with the fracture site level.

In cases where the device is used to lengthen a thigh, the top end of the tubular driver is left to stick a little bit out of the skin. It is covered by a sterile dressing and is opened only when accomplishing the daily lengthening, which is usually from 1 to 1,5 mm. The driver is unscrewed and removed after the lengthening has been accomplished, and the wound is sutured.

In all other cases the tubular driver is removed right upon the compression is over, and the upper end of the device is covered by the soft tissues.

The intramedullary device for fixation, compression and traction of the femur possesses the possibilities both of the interlocking nails for static fixation and those of the external fixators for dynamic compression and traction, avoiding at the same time the above-mentioned disadvantages of those methods. That is why it takes priority over the interlocking nails or external fixators in all cases, except for cases of infected fractures or infected non-union fractures.

WO 00/27298

PCT/BC99/00025

LITERATURE

1. CAMBELL'S OPERATIVE ORTHOPAEDICS Ninth Edition 1998
2. Grosse.A. : Manual for osteosynthesis for femoral and tibial shaft fractures., Kiel, West Germany, 1981, Howmedica international, inc.
3. Russel.T.A. and Taylor.J.C. : Russel - Taylor interlocking medullary nail system. Richards Medical Co, Memphis, 1984
4. Zickel.R.E. : A new fixation for subtrochanteric fractures of the femur; a preliminary report. Clin. Orthop. 54:115, 1967
5. Zickel.R.E. : An intramedullary fixation device for proximal part of the femur: nine years experience. J. Bone Joint. Surg. 58-A.866, 1976

WO 00/27298

PCT/BG99/00025

PATENT CLAIM

An intramedullary device for fixation, compression and traction of the femur, *characterized by* that it consists of two metal tubes (4) and (5) with different diameters and the profile of a Kuntscher nail, the inner metal tube or slider (5) having in its top inside end threads with a feeding screw (1) disposed therein, the top end of the feeding screw passing through a bearing (2) with a stopper (3) under and above it, while under the bottom end of the screw (1) on the opposite sides of the outer metal tube (4) there are drilled holes at an equal distance one from the other, such holes being drilled in the distal part of the slider (5) as well, while under the distal hole of the outer tube (4) and above the proximal hole of the slider (5) there is cut a bilateral longitudinal slot.

WO 00/27298

PCT/BG99/00025




Fig. 1

INTERNATIONAL SEARCH REPORT

International Application No

PCT/BG 99/00025

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A61B17/72

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 85 33 134 U (INSTITUT STRAUMANN) 3 April 1986 (1986-04-03) page 13, line 16 -page 15, line 15; figure 5	1
A	WO 96 35387 A (UNIVERSITY OF WESTERN AUSTRALIA) 14 November 1996 (1996-11-14) page 4, line 15 -page 5, line 19; figure 1	1

☐ Further documents are listed in the continuation of box C.

Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"Z" document member of the same patent family

Date of the actual completion of the international search

20 March 2000

Date of mailing of the international search report

28/03/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Nice, P

INTERNATIONAL SEARCH REPORT

Information on patent family members			Int: onal Application No PCT/BG 99/00025	
Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 8533134 U		03-04-1986	CH 666176 A	15-07-1988
			DE 3541597 A	05-06-1986
			FR 2573978 A	06-06-1986
			GB 2167963 A,B	11-06-1986
			US 4875475 A	24-10-1989
WO 9635387 A		14-11-1996	AU 5492996 A	29-11-1996